

BTS PANEL ANTENNA

1800 MHz SINGLE BAND GSM ANTENNA

Model:KE1721X6520-DT0



Dual-Polarization Antenna, 1710-2170 MHz, 65° horizontal beamwidth, Fixed electrical tilt

- Rugged and reliable design
- Excellent passive intermodulation suppression

Electrical Specifications			
Band Of Operation, MHz	1710 ~ 1880	1850 ~ 1990	1920 ~ 2170
Gain in dBi	20	20.2	20.7
HBW(degrees)	65	65	65
VBW(degrees)	3.5	3.2	3
Electrical Tilt (Degrees)	0	0	0
Polarization (Degrees)	± 45	± 45	± 45
Impedance (Ohms)	50	50	50
1st Null Fill dB	> -25	> -25	> -25
VSWR	≤ 1.4	≤ 1.4	≤ 1.4
Intermodulation IM3(@2x43 dbm)	< - 107	< - 107	< - 107
Side Lobe Suppression; dB (First sidelobe above horizon)	0°→≥16	0°→≥16	0°→≥16
	5°→≥15	5°→≥15	5°→≥15
	10°→≥14	10°→≥14	10°→≥14
Cross Polar Discrimination,dB	> 15	> 15	> 15
Front-to-Back Ratio;dB	>25	>25	>25
Isolation Between Ports,dB	>30	>30	>30
Max. Input Power (Watts)	200	200	200

1800 MHz SINGLE BAND GSM ANTENNA

Model:KE1721X6520-DT0

Mechanical Specifications	
Dimensions (L x W x H in mm)	2574X195X 95
Weight(Kgs):	
Antenna	11
Bracket	5
Radome Material	Fiberglass
Connector Type	7/16 DIN female
Connector Position	Bottom
No. of connectors	2
Operating Temperature(°C)	- 40 ° to + 60 °
Rated Wind Speed(Km/Hr)	200
Lightening Protection	Direct ground