

BTS PANEL ANTENNA


900/1800MHz DUAL BAND GSM ANTENNA

Model:KE0809/1721DX6517/18-DE10/E8



Dual-Polarization Antenna, 65° horizontal beamwidth, variable electrical tilt

- Field adjustable electrical tilt
- Rugged and reliable design
- Excellent passive intermodulation suppression



Electrical Specifications					
Band Of Operation, MHZ	824~896	870~960	1710~1880	1850~1990	1920~2170
Gain in dBi	16.5	17	17	17.8	18
HBW(degrees)	65	63	66	64	62
VBW(degrees)	8	7.5	6	5.7	5.3
Electrical Tilt (Degrees)	0 ~ 10	0 ~ 10	0 ~ 8	0 ~ 8	0 ~ 8
Polarization (degrees)	± 45				
Impedance(Ω)	50				
1st Null Fill (dB)	> -25				
VSWR	< 1.5				
Intermodulation IM3(@2x43 dbm)	< - 107				
Side Lobe Suppression; dB	≥16				
Cross Polar Discrimination,dB	> 15				
Front-to-Back Ratio (dB)	≥25				
Isolation Between Ports (dB)	≥30				
Max. Input Power (Watts)	200				

900/1800MHz DUAL BAND GSM ANTENNA

Model:KE0809/1721DX6517/18-DE10/E8

Mechanical Specifications

Dimensions (L x W x H in mm)	2090X306X140
Weight(Kgs): Antenna Bracket	26.1 4.0
Radome Material	ABS Plastic/Fiberglass
Connector Type	7/16 DIN female
Connector Position	Bottom
No. of connectors	4
Operating Temperature(°C)	- 40 ° to + 60 °
Rated Wind Speed(Km/Hr)	216
Lightening Protection	Direct ground

Radiation Pattern

