

BTS PANEL ANTENNA

900 MHz SINGLE BAND CDMA/GSM ANTENNA

Model:KE08X9016-DT0/3/4/5



Dual-Polarization Antenna, 900MHz, 90° horizontal beamwidth, Fixed electrical tilt

- Rugged and reliable design
- Excellent passive intermodulation suppression

Electrical Specifications

Band Of Operation, MHz	806 ~ 900
Gain in dBi	16
HBW(degrees)	90
VBW(degrees)	7
Electrical Tilt (Degrees)	0/3/4/5
Polarization (Degrees)	± 45
Impedance (Ohms)	50
1st Null Fill dB	>-25dB
VSWR	≤ 1.4
IM3(@2x43 dbm)	< - 107
Upper Side Lobe Suppression; dB	≥15
Cross Polar Discrimination,dB	Main > 15dB, ±60°>10dB or ±30°>10dB
Front-to-Back Ratio;dB	≥23
Isolation Between Ports,dB	≥30
Max. Input Power per Input (Watts)	500

900 MHz SINGLE BAND CDMA/GSM ANTENNA
Model:KE08X9016-DT0/3/4/5

Mechanical Specifications	
Dimensions (L x W x H in mm)	2520 X 280 X 161
Weight(Kgs):	
Antenna	14
Bracket	5
Radome Material	Fiberglass
Connector Type	7/16 DIN female
Connector Position	Bottom
No. of connectors	2
Operating Temperature(°C)	- 40 ° to + 60 °
Rated Wind Speed(Km/Hr)	198
Lightening Protection	Direct ground