

BTS PANEL ANTENNA

900 MHz SINGLE BAND GSM ANTENNA

Model:KE900X65-18T6D



Dual-Polarization Antenna, 900MHz, 65° horizontal beamwidth, Fixed electrical tilt

- Rugged and reliable design
- Excellent passive intermodulation suppression

General Specifications

Band Of Operation, MHz	870 ~ 960
Gain in dBi	18
HBW(degrees)	65
VBW(degrees)	7
Electrical Tilt (Degrees)	6
Polarization (Degrees)	± 45
Impedance (Ohms)	50
1st Null Fill dB	>-25dB
VSWR	≤ 1.4
IM3(@2x43 dbm)	< - 107
Upper Side Lobe Suppression; dB	≥16
Cross Polar Discrimination,dB	Main > 15dB, ±60°>10dB or ±30°>10dB
Front-to-Back Ratio;dB	>25
Isolation Between Ports,dB	>30
Max. Input Power per Input (Watts)	500

900 MHz SINGLE BAND GSM ANTENNA
Model:KE900X65-18T6D

Mechanical Specifications	
Dimensions (L x W x H in mm)	2520 X 265 X 150
Weight(Kgs):	
Antenna	14
Bracket	5
Radome Material	Fiberglass
Connector Type	7/16 DIN female
Connector Position	Bottom
No. of connectors	2
Operating Temperature(°C)	- 40 ° to + 60 °
Rated Wind Speed(Km/Hr)	216
Lightening Protection	Direct ground