

BTS PANEL ANTENNA

2400 MHz SINGLE BAND ANTENNA

Model:KE24X6517-DT0/3/6



Dual-Polarization Antenna, 2400-2500MHz, 65° horizontal beamwidth, Fixed electrical tilt


- Rugged and reliable design
- Excellent passive intermodulation suppression

Electrical Specifications	
Band Of Operation, MHz	2400 ~ 2500
Gain in dBi	17
HBW(degrees)	65
VBW(degrees)	9.5
Electrical Tilt (Degrees)	0/3/6
Polarization (Degrees)	± 45
Impedance (Ohms)	50
1st Null Fill dB	>-25dB
VSWR	≤ 1.5
IM3(@2x43 dbm)	< - 107
Upper Side Lobe Suppression; dB	≥15
Cross Polar Discrimination,dB	Main > 15dB, ±60°>10dB or ±30°>10dB
Front-to-Back Ratio;dB	≥25
Isolation Between Ports,dB	≥30
Max. Input Power per Input (Watts)	100


2400 MHz SINGLE BAND GSM ANTENNA
Model:KE24X6517-DT0/3/6

Mechanical Specifications	
Dimensions (L x W x H in mm)	886 X 195 X 95
Weight(Kgs):	
Antenna	4.8
Bracket	5
Radome Material	ABS Plastic /Fiberglass
Connector Type	7/16 DIN female
Connector Position	Bottom
No. of connectors	2
Operating Temperature(°C)	- 40 ° to + 60 °
Rated Wind Speed(Km/Hr)	198
Lightening Protection	Direct ground

Radiation Pattern



2400MHz



2500MHz