

BTS PANEL ANTENNA

1800 MHz SINGLE BAND GSM ANTENNA

Model:KE1721DX6518-DE10



Dual-Polarization Antenna, 1710-2170 MHz, 65° horizontal beamwidth, variable electrical tilt

- Field adjustable electrical tilt
- Rugged and reliable design
- Excellent passive intermodulation suppression

Electrical Specifications


Band Of Operation, MHz	1710 ~ 1880	1850 ~ 1990	1920 ~ 2170
Gain in dBi	17	17.3	17.5
HBW(degrees)	67	65	62
VBW(degrees)	7.5	7	6.5
Electrical Tilt (Degrees)	0 ~ 10	0 ~ 10	0 ~ 10
Polarization (Degrees)	± 45	± 45	± 45
Impedance (Ohms)	50	50	50
1st Null Fill dB	> -25	> -25	> -25
VSWR	< 1.5	< 1.5	< 1.5
Intermodulation IM3(@2x43 dbm)	< - 107	< - 107	< - 107
Side Lobe Suppression; dB (First sidelobe above horizon)	0°→≥15	0°→≥15	0°→≥15
	5°→≥14	5°→≥14	5°→≥14
	10°→≥13	10°→≥13	10°→≥13
Cross Polar Discrimination,dB	> 15	> 15	> 15
Front-to-Back Ratio;dB	>25	>25	>25
Isolation Between Ports,dB	>30	>30	>30
Max. Input Power (Watts)	300	300	300

1800 MHz SINGLE BAND GSM ANTENNA


Model:KE1721DX6518-DE10

Mechanical Specifications	
Dimensions (L x W x H in mm)	1554X195X 95
Weight(Kgs):	
Antenna	9.5
Bracket	5
Radome Material	ABS Plastic
Connector Type	7/16 DIN female
Connector Position	Bottom
No. of connectors	2
Operating Temperature(°C)	- 40 ° to + 60 °
Rated Wind Speed(Km/Hr)	200
Lightening Protection	Direct ground


Radiation Pattern



1710~1880MHz



1850~1990MHz



1920~2170MHz