Quality Assurance

Our strong focus on manufacturing process and quality assurance enables us to supply high quality material and deliver cost effective solution. Our manufacturing practice has been technology driven and to stay at the fore front of innovation, we continuously invest in Research and Development. Our quality management system ensures high level of quality by inspection of incoming material and mandatory quality checks at every stage throughout the manufacturing process. Our highly equipped quality and testing facility enables us to deliver superior quality products conforming to Indian/International standards and achieve total customer satisfaction.

Inward inspection

Upon receipt of basic raw materials our quality team will take a random sample subjected for chemical analysis test conducted on computerized spectrometer to ensure the raw materials as per the IS standards apart from that the material will also been tested on UTS machine to check ultimate tensile strength of the raw material after satisfactory report of the samples the same will be cleared for production.

In process Inspection:

Online testing will be carried out at every stage with suitable jigs & gauges to ensure the required specifications as defined in the standards.

Final Inspection:

Final inspection check is carried out to ensure that Product Quality is in conformance with specified requirements.

Inspection and Test Reports / Records are maintained to establish that the product has passed inspection and testing in accordance criteria defined in the Inspection and Testing Procedures. Records are maintained for calibration and verification of monitoring and measuring equipments. We are ISO 9001-2008 certified for well maintained Quality Management Systems by NQA-UKAS.

Kadevi test equipment include:

- 1. Latest emission spectrometer for instant and accurate chemical analysis of metal.
- 2. Physical testing facilities like ultimate tensile test, bend test, hardness test and impact test at Lab.
- 3. Other measuring Instrument, Gauges etc. to confirm to Specification & Drawings





Corporate Office: Kadevi Industries Limited A1 - A2, Electronic Complex, Kushaiguda, Hyderabad, A.P. India - 500062. Telephone: +91 40 27121450, Fax +91 40 27121657 Email : steelrollingmill@kadevigroup.com

Branches:


Delhi Hyderabad Chennai Bangalore

Works:

S.No 146&147, Ankireddypally, Keesara mandal, R.R District A.P. India - 501 301 Telephone: 08418 - 284963



ISO 9001-2008 & ISO 14001-2004 & BS OHSAS 18001-2007 **CERTIFIED COMPANY**






Steel Rolling Mill Division CUSTOMER SATISFACTION WITH ENHANCED QUALITY AND RELIABILITY







Steel Rolling Mill Division

About Kadevi

Kadevi was established in 1964 and started as a small scale industry manufacturing of Communication Antennas and Pneumatic Telescopic Masts. Subsequently the company further expanded its wings into various manufacturing & service fields.

Kadevi has rapidly grown to a large scale industry just in 3 years and has received several awards and became pioneer in all fields. Today the company is having 1000 plus strong manpower.

Manufacturing Divisions

Steel Rolling Mill Division

• 3 No's Heavy Duty Straightening machines.

Production Process

- Towers & Galvanising
- Telescopic & Guyed Masts
- Antenna Systems
- Steel Rolling Mill
- Fasteners
- Generators

IS 2062 : 2006

Infrastructure

Online Hot Saw Machine.

- Service Divisions
- Transmission & Distribution
- Tower Installations
- EPC & TSP

Kadevi is having a rare combination of full scaled infrastructure under one roof with state of art inhouse facilities right from manufacturing of steel

sections, fabrication of towers & structures, Hot dip galvanising, Fasteners & Generators at Ankireddypally Plant. These facilities are fully

Our rolling mill is fully automatic right from billet loading till extrusion of sections with state of art infrastructure with expertise manpower. Our mill is


capable of producing 60,000 metric tons of structural steel of various sections, channels and beams. Our angles are BIS certified as per



Cooling Bed:

The cooling bed is used to uniformly air cool the sections after cooling transporting the same in a phased manner from the entry to discharge size. This cooling bed impart better straightness in material with improvised metallurgical properties as the sections are uniformity cooled.





SIZE mm

mm x mm

40X40

45X45

50 x 50

55 x 55

60 x 60

Mass

(M)



	Kg
	2
MC 75	7.14
MC 100	9.56
MC 125	13.1
MC 150	16.8
	· · · · ·

Product

Range

Product Range	Mass (M)	Sectional Area(a)	Dimensions						
			D	в	t	т	Flange Slope	R1	R2
	Kg	cm2	mm	mm	mm	mm	Deg	mm	mm
	2	3	4	5	6	7	8	9	10
MB 100	8.9	11.4	100	50	4.7	7	98	9	4.5
MB 125	13.3	17	125	70	5	8	98	9	4.5
MB 150	15	19.1	150	75	5	8	98	9	4.5
MB 175	19.6	25	175	85	5.8	9	98	10	5
MB 200	24.2	30.8	200	100	5.7	10	98	11	5.5

Kadevi reserves the right to change without notice the specifications of the production range.

rect	Product Range	Mass (M)	Sectional Area(a)	Dimensio				ensions	ons		
k the				D	в	t	т	Flange Slope	R1	R2	
		Kg	cm2	mm	mm	mm	mm	Deg	mm	mm	
		2	3	4	5	6	7	8	9	10	
	MB 100	8.9	11.4	100	50	4.7	7	98	9	4.5	
	MB 125	13.3	17	125	70	5	8	98	9	4.5	
	MB 150	15	19.1	150	75	5	8	98	9	4.5	
	MB 175	19.6	25	175	85	5.8	9	98	10	5	
	MB 200	24.2	30.8	200	100	5.7	10	98	11	5.5	

Straightening: Straightening Machine straightens all

the deformed products like Angles Channels & I-Beams after cooling.

Packing: After ensuring the corre straightness of section we pack material in 2.5 to 3MT bundles.



Billet Cutting

Completely Integrated with 3 EOT Cranes, 3 Mobile Cranes, suspended weighing machine and in-house Weighbridge.

equipped to ensure the highest level of quality and delivery timelines of customer.

20 mtrs X3.4 double zone pusher type Reheating Oil Fired Furnace.

Inhouse work shop equipped with full scaled machinery for rolls tooling.

18 Inches Mill Stand attached with Totally automatic conveyor.

• Cooling Bed with size 27 mtrs x 9 mtrs with automatic coveyors.

We receive billets in 6 mts & 12 mts lengths from which we cut the billet to predetermine size to get correct length & dimension of the structure.

Billet Re-heating:

The Billet is fed into reheating furnace till it obtains the job temperature of 1050°C. After obtaining the temperature The billet is ejected out to the conveyor to pass through mill stands.



Billet Rolling:

The Hot billet is fed into the rolling process, in which billet is passed through the rollers clamped to the Six Stands to get the predetermined size.

Online Hot-Saw Machine:

Our Online Hot-Saw is to cut every section to the precised size as well as to trim front & Rear End of the structure.







Range of Products Equal Leg Angles

		_	<u> </u>					
	Thick	ness	mm	Weight Kg./Mtr				
4	5	6	8	10	12	16	20	
2.40	3.00	3.60			7			
2.70	3.40	4.00	*	*	*	*	*	
3.00	3.80	4.50	*	*	*	*	*	
3.30	4.10	4.90	6.40	*	*	*	*	
3.60	4.50	5.40	7.00	*	*	*	*	
3.90	4.90	5.80	7.70	9.40	*	*	*	
*	5.30	6.30	8.30	10.20	*	*	*	
*	5.70	6.80	8.90	11.00	*	*	*	
*	*	7.30	9.60	<mark>11.8</mark> 0	14.00	*	*	
*	*	8.20	10.80	<mark>13.</mark> 40	15.80	*	*	
*	*	9.20	12.10	14.90	17.70	*	*	
*	*	*	13.40	<mark>1</mark> 6.60	19.70	*	*	
*	*	*	15.90	19.70	23.50	*	*	
*	*	*	*	22.90	27.30	35.80	44.10	
	4 2.40 2.70 3.00 3.30 3.60 3.90 * * * * *	4 5 2.40 3.00 2.70 3.40 3.00 3.80 3.30 4.10 3.60 4.50 3.60 4.50 3.90 4.90 * 5.30 * 5.70 * 5.70 * * * * * * * * * * * * * *	4 5 6 2.40 3.00 3.60 2.70 3.40 4.00 3.00 3.80 4.50 3.00 3.80 4.50 3.30 4.10 4.90 3.60 4.50 5.40 3.60 4.50 5.40 3.90 4.90 5.80 * 5.30 6.30 * 5.70 6.80 * 5.70 8.20 * * 9.20 * * * * * *	Hickness mm 4 5 6 8 2.40 3.00 3.60 2.70 3.40 4.00 * 3.00 3.80 4.50 * 3.00 3.80 4.50 * 3.00 3.80 4.50 * 3.00 4.10 4.90 6.40 3.60 4.10 4.90 6.40 3.60 4.50 5.40 7.00 3.60 4.50 5.40 7.00 3.90 4.90 5.80 7.70 4.90 5.80 8.30 * 5.70 6.80 8.90 * 5.70 6.80 9.60 * 7.30 9.60 * 8.20 10.80 * * 9.20 12.10 * * * 13.40	4 5 6 8 10 2.40 3.00 3.60 2.70 3.40 4.00 * * 3.00 3.80 4.50 * * 3.00 3.80 4.50 * * 3.00 3.80 4.50 * * 3.30 4.10 4.90 6.40 * 3.30 4.10 4.90 6.40 * 3.60 4.50 5.40 7.00 * 3.90 4.90 5.80 7.70 9.40 * 5.30 6.30 8.30 10.20 * 5.70 6.80 8.90 11.00 * 5.70 6.80 8.90 11.80 * 8.20 10.80 13.40 * 9.20 12.10 14.90 * * 13.40 16.60	Weight 4 5 6 8 10 12 2.40 3.00 3.60 4.00 $*$ $*$ $*$ 2.70 3.40 4.00 $*$ $*$ $*$ 3.00 3.80 4.50 $*$ $*$ $*$ 3.00 3.80 4.50 $*$ $*$ $*$ 3.00 3.80 4.50 $*$ $*$ $*$ 3.00 3.80 4.50 $*$ $*$ $*$ 3.00 4.90 6.40 $*$ $*$ 3.30 4.10 4.90 6.40 $*$ $*$ 3.60 4.50 5.40 7.00 $*$ $*$ 3.60 4.50 5.40 7.00 $*$ $*$ 3.60 4.50 5.40 7.00 $*$ $*$ 3.60 4.50 5.40 7.00 $*$ $*$ 3.60 4.50 5.40 7.00 $*$ $*$ 3.90 4.90 5.80 7.70 9.40 $*$ $*$ 5.30 6.30 8.300 10.20 $*$ $*$ 5.70 6.80 8.900 11.80 14.00 $*$ $*$ 8.20 10.80 13.40 15.80 $*$ $*$ 9.20 12.10 14.90 17.70 $*$ $*$ $*$ 13.40 16.60 19.70 $*$ $*$ $*$ 15.90 19.70 23.50	Weight Kg./M 4 5 6 8 10 12 16 2.40 3.00 3.60 4.00 $*$ $*$ $*$ $*$ 2.70 3.40 4.00 $*$ $*$ $*$ $*$ $*$ 3.00 3.80 4.50 $*$ $*$ $*$ $*$ 3.00 3.80 4.50 $*$ $*$ $*$ $*$ 3.00 3.80 4.50 $*$ $*$ $*$ $*$ 3.00 3.80 4.50 $*$ $*$ $*$ $*$ 3.00 4.90 6.40 $*$ $*$ $*$ 3.60 4.50 5.40 7.00 $*$ $*$ $*$ 3.60 4.50 5.40 7.00 $*$ $*$ $*$ 3.60 4.50 5.40 7.00 $*$ $*$ $*$ 3.60 4.50 5.40 7.00 $*$ $*$ $*$ 3.90 4.90 5.80 7.70 9.40 $*$ $*$ $*$ 5.30 6.30 8.30 10.20 $*$ $*$ $*$ 5.70 6.80 8.90 11.00 $*$ $*$ $*$ $*$ 7.30 9.60 11.80 14.00 $*$ $*$ $*$ 9.20 12.10 14.90 17.70 $*$ $*$ $*$ $*$ 13.40 16.60 19.70 $*$ $*$ $*$ $*$ 15.90 19.70 23.50 $*$	

MEDIUM WEIGHT CHANNELS

	Dimensions						
	D	в	t	т	Flange Slope	R1	R2
cm2	mm	mm	mm	mm	Deg	mm	mm
3	4	5	6	7	8	9	10
9.1	75	40	4.8	7.5	96	8.5	2.4
12.2	100	50	5	7.7	96	9	2.4
16.7	125	65	5.3	8.2	96	9.5	2.4
21.3	150	75	5.7	9	96	10	2.4
	3 9.1 12.2 16.7	Area(a) D cm2 mm 3 4 9.1 75 12.2 100 16.7 125	Area(a) D B Cm2 mm mm 3 4 5 9.1 75 40 12.2 100 50 16.7 125 65	DBtcm2mmmmmm34569.175404.812.210050516.7125655.3	D B t T cm2 mm mm mm mm 3 4 5 6 7 9.1 75 40 4.8 7.5 12.2 100 50 5 7.7 16.7 125 65 5.3 8.2	Dimensions D B t T Flange Slope cm2 mm mm mm mm Deg 3 4 5 6 7 8 9.1 75 40 4.8 7.5 96 12.2 100 50 5 7.7 96 16.7 125 65 5.3 8.2 96	Area(a) D B t T Flange Slope R1 cm2 mm mm mm mm Deg mm 3 4 5 6 7 8 9 9.1 75 40 4.8 7.5 96 8.5 12.2 100 50 5 7.7 96 9 16.7 125 65 5.3 8.2 96 9.5

BEAM SECTION (Joist)

* The standard length for all dimensions rage from 10-13 Mtr., However Kadevi can supply fixed length ranging from 6-13 Mtr. As required.